

S-96,247
IL-10758

UNIVERSALLY ORIENTED RENEWABLE LIQUID MIRROR

BY

Dmitri D. Ryutov (USA)
1831 5th Street
Livermore, CA 94550

Arthur Toor (USA)
3383 N. Bayview Rd.
Waldport, OR 97394

UNIVERSALLY ORIENTED RENEWABLE LIQUID MIRROR

[0001] The United States Government has rights in this invention pursuant to Contract No. W-7405-ENG-48 between the United States Department of Energy and the University of California for the operation of Lawrence Livermore National Laboratory.

CROSS-REFERENCE TO RELATED APPLICATIONS

[0002] This application claims the benefit of U.S. Provisional Application No. 60/258,192, filed 12/22/2000, and entitled "Renewable Thin-Liquid-Film Reflecting Apparatus," which is incorporated herein by this reference. U.S. Patent Application No. xx/xxx,xxx, filed 12/xx/2001 entitled "Renewable Thin-Liquid-Film Reflection Grating" and U.S. Patent Application No. xx/xxx,xxx, filed 12/xx/2001 entitled "Renewable Thin Film Liquid Reflecting Zone Plate" describing related inventions are being filed simultaneously with this application. The specification, drawings, and disclosure of U.S. Patent Application No. xx/xxx,xxx, filed 12/xx/2001 entitled "Renewable Thin-Liquid-Film Reflection Grating" and U.S. Patent Application No. xx/xxx,xxx, filed 12/xx/2001 entitled "Renewable Thin Film Liquid Reflecting Zone Plate" are incorporated herein by this reference.

BACKGROUND

Field of Endeavor

[0003] The present invention relates to mirrors and more particularly to a universally oriented liquid mirror.

State of Technology

[0004] An arbitrarily oriented mirror is an important element of an optical system. It allows an arbitrary transformation of a light beam. There exist high quality solid mirrors, both planar and shaped which can be arbitrarily oriented in the gravity field. However, in applications where one deals with high-power pulses of radiation these mirrors will be damaged and would require replacement after every pulse, introducing significant operational expenses. There exists also planar and parabolic (rotating) liquid mirrors, as well as liquid mirrors controlled by $j \times B$ forces, but these mirrors are suitable only for a specific ("face up") orientation in the gravity field.

SUMMARY

[0005] Features and advantages of the present invention will become apparent from the following description. Applicants are providing this description, which includes drawings and examples of specific embodiments, to give a broad representation of the invention. Various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this description and by practice of the invention. The scope of the invention is not intended to be limited to the particular forms disclosed and the

invention covers all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the claims.

[0006] The present invention provides a universally oriented liquid mirror. The mirror comprises a liquid and a penetrable unit. A system operatively connects the liquid to the penetrable unit to provide a mirror that can be universally oriented.

[0007] The invention is susceptible to modifications and alternative forms. Specific embodiments are shown by way of example. It is to be understood that the invention is not limited to the particular forms disclosed. The invention covers all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The accompanying drawings, which are incorporated into and constitute a part of the specification, illustrate specific embodiments of the invention and, together with the general description of the invention given above, and the detailed description of the specific embodiments, serve to explain the principles of the invention.

FIG. 1 illustrates an embodiment of a planar renewable mirror system.

FIG. 2 shows a liquid film over a solid substrate.

FIG. 3 depicts dispersion curves for capillary oscillations of mercury film of various depths.

FIG. 4 depicts dispersion relation presented in the dimensionless form.

FIG. 5 illustrates creating a quasi-planar mirror by an electrostatic correction of the meniscus.

FIG. 6 illustrates creating a focusing mirror by electrostatic forces acting on the surface of a conducting fluid, with a control electrode situated above the mirror surface.

FIG. 7 illustrates creating a focusing mirror by electrostatic forces acting on the surface of a dielectric fluid, with a control electrode situated underneath the solid substrate.

FIG. 8 illustrates the possibility of creating a tilted renewable planar mirror by compensating the gravity force by a $\mathbf{j} \times \mathbf{B}$ force in a conducting fluid.

FIG. 9 illustrates another embodiment of a system incorporating the present invention.

FIG. 10 illustrates an additional embodiment of a system incorporating the present invention.

FIG. 11 illustrates an additional embodiment of a system incorporating the present invention.

FIG. 12 illustrates creating a shaped renewable liquid mirror by using a shaped substrate.

DETAILED DESCRIPTION OF THE INVENTION

[0009] Referring now to the drawings, to the following detailed information, and to incorporated materials; a detailed description of the invention, including specific embodiments, is presented. The detailed description serves to explain the

principles of the invention. The invention is susceptible to modifications and alternative forms. The invention is not limited to the particular forms disclosed. The invention covers all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the claims.

[0010] Referring now to FIG. 1, an embodiment of a system incorporating the present invention is illustrated. The system is generally designated by the reference numeral 10. The system 10 is a planar renewable universally oriented liquid mirror. The planar renewable mirror system is shown with an upside-down orientation in FIG. 1. The universally oriented liquid mirror 10 includes a liquid 11 contained by a porous unit 12. The porous unit 12 maintains operability of the liquid mirror 10 in all orientations.

[0011] The liquid film planar renewable mirror system 10 illustrated in FIG. 1 will now be described in greater detail. A system for creating liquid mirrors for X-ray and optical wavelengths that can be arbitrarily oriented with respect to gravity is provided and used to produce the liquid film planar renewable mirror 10. The system uses a porous substrate 12, ~1 mm thick. A piston 15 presses the working fluid through the substrate, creating a liquid film with a thickness, which is a few times the diameter of the characteristic pore size. Capillary forces in combination with viscous damping smooth all small-scale non-uniformities and create a surface of an optical quality. After the passage of the optical pulse, the film is pulled back by reversing the piston and the same sequence is repeated. The time for the in-out motion of the fluid will be shorter than the time

for the film to flow under the action of gravity. For the "upside-down" configuration, the in-out time must be also shorter than the e-folding time for long-wavelength, Rayleigh- Taylor unstable perturbations. For centimeter-size mercury mirrors, 30 micron thick, the in-out time can be as long as 0.1 s. By shaping the surface of the porous substrate, one can create curved mirrors. In some configurations, the gravity-driven flow can be suppressed by driving the current through the film and stopping the gravity-driven flow by the $\mathbf{J} \times \mathbf{B}$ force.

[0012] The mirror 10 is particularly useful in situations where a conventional mirror would experience problems. The 3rd generation light sources, such as the Advanced Photon Source at Argonne National Laboratory, are capable of providing sufficient dose to optical components to create permanent damage. Such damage will cause operational limitation that must be overcome to realize the potential of the 4th generation light sources that are in the planning process both in US and Germany. The liquid mirror provides the unique feature of renewing the optical surface in situ between successive intense light or x-ray pulses. Other applications include the using the renewable liquid mirror as an element of optical diagnostics in high-energy-density experiments, like the National Ignition Facility at Lawrence Livermore National Laboratory, Z facility at Sandia, and others, where these mirrors could be placed much closer to the point of the energy release than conventional solid-state mirrors. Systems where damage to the optical elements is a serious design constraint, include also rep-rate lasers for commercial applications.

[0013] Referring again to FIG. 1, the liquid film 13 is formed by pressing a working liquid 11 through a porous substrate 12 by a piston 15. The working liquid 11 shown in FIG. 1 is mercury. In other embodiments of the invention the working fluid is composed of other materials that provide reflectivity. The working fluid in other embodiments can be conducting liquids including Gallium; NaK alloy (40 to 90% of K). The working fluid in other embodiments can be dielectric liquids including various alcohols, from ethyl alcohol C_2H_6O to benzyl alcohol C_7H_8O ; glycerin; heavy hydrocarbons, like C_9H_{20} .

[0014] The piston 15 moves within a cylinder 14. Before the gravitational instability has developed, the piston 15 sucks the liquid 13 back, and the cycle repeats. In the embodiment shown, the substrate 12 is made of fused capillaries of the same radius r_{cap} . In other embodiments, different porous substrates 12 can be used. In other embodiments, the system operates to push and pull the liquid not by a piston, but by a flexible membrane driven by actuators situated behind it.

[0015] The embodiment illustrated in FIG. 1 presents a new class of centimeter-size renewable optical elements consisting in most cases of thin liquid films over porous substrates, which can be used in a rep-rate mode. Between two successive pulses the optical elements can be created anew. The film thickness of the system 10 is in the range from a few microns to a hundred of microns. The film behavior is strongly affected by capillary forces. Electrostatic, $j \times B$, and capillary forces are used to control the shape of the surface of the film 13. Optical

elements, in most cases, can be arbitrarily oriented with respect to the gravitational force. The acronym "CAMEL" - - CAPillary-Magneto-ELectrostatic" is used to designate this new class of optics.

[0016] The word "capillary" as used herein in two senses. First, it is used as a noun, to designate a thin channel in a solid material. Second, following a long tradition, it is used as an adjective, to designate short-wavelength perturbations on the free surface of the liquid ("capillary waves"). The restoring force for this type of waves is provided by surface tension sometimes called a "capillary force," whence the "capillary waves."

[0017] Renewing an optical element after each pulse has particular utility in developing optics for the fourth-generation light sources, such as LCLS and XFEL, where extremely intense beams of 8-10 keV photons will be generated. In the LCLS facility, for example, the flux of the 8-keV photons will be up to $1.4 \cdot 10^{14}$ W/cm² within a 250 fs pulse, with total fluence during the pulse reaching 40 J/cm². Such fluences may cause a serious damage to materials that can be used as mirrors, lenses, diffraction gratings, and other optical elements. The pulses will follow at a frequency ~ 100 Hz. Therefore, if these high-fluence beams are used without their preliminary significant attenuation, it is necessary to come up with some concept that will allow replacing optical elements after each pulse. In our approach, these elements are created anew after each pulse, on the surface of a liquid, without causing any damage to permanent structures.

[0018] The CAMEL optics provide qualitatively new and important features and can become the enabling technology for a broad variety of applications, many of which are difficult to foresee at this time. Some of the CAMEL optics applications include:

- 1) Renewable X-ray optics for ultra-intense x-ray free electron lasers (the needs of LCLS initially stimulated us to consider pulse-to-pulse renewable capillary diffraction gratings and gave rise to the first steps in the analysis of the CAMEL concept);
- 2) Renewable optics for pulsed and rep-rate high-power lasers at longer wavelengths, including the visible and infrared range.
- 3) Configurations used to create adaptive optics for steady-state low-intensity sources.

[0019] CAMEL optics for rep-rate applications allows one to monitor and change the parameters of the optical system between two successive pulses at a frequency of ~ 100 Hz.

[0020] Engineering equations required for design of the CAMEL optics are provided below.

Basic Notations Used In Description

[0021] In the general equations we use the CGS system of units. In "practical" estimates we use mixed units specified in each case.

- a - distance of the conducting ring from the film surface
- b - thickness of the substrate
- c - speed of light

g – gravitational acceleration
 h – thickness of a liquid film
 k – wave number of perturbations
 k^* – critical wave number (Equation (2.2))
 r_{cap} – inner radius of the capillary
 B – magnetic field strength
 C_p – thermal capacity per unit volume
 D_m – magnetic diffusivity
 E – (1) electric field strength, and (2) Young's modulus for the substrate
 R – (1) radius of a mirror, and (2) radius of an electrically charged ring
 S – sound speed
 U – voltage applied between the conducting ring and working liquid
 α – capillary constant
 β – volumetric thermal expansion coefficient
 Δb – deformation of the substrate
 Δh – (1) variation of the film thickness, and (2) thickness of the film layer heated by the laser
 κ_b – Boltzmann constant
 η – filling factor of the substrate (a fraction of the surface occupied by capillary holes)
 λ – spatial period of the diffraction grating
 λ_x – wavelength of x-ray radiation (or, generally, of the incident light)
 ν – kinematic viscosity
 ξ – displacement of a liquid element in the perturbation
 ρ – liquid density
 σ – electrical conductivity
 τ – viscous dissipation time (Equation (8))
 χ – thermal diffusivity
 ω – frequency of surface waves
 ω_{vibr} – frequency of vibrations of mechanical structure

[0022] Although there exists a large variety of liquids suitable for the CAMEL optics, the numerical estimates set out herein only apply to one liquid, namely mercury. Parameters of the mercury required for discussion are listed in Table 1. In cases where we discuss dielectric liquids we assume that their dielectric constant is not much greater than 1, $\epsilon-1 \sim 1$.

Table 1. Room Temperature Parameters for Mercury

Density	$\rho = 13.6 \text{ g/cm}^3$
Kinematic viscosity	$\nu = 1.2 \times 10^{-3} \text{ cm}^2/\text{s}$
Electrical conductivity	$\sigma = 1 \times 10^{16} \text{ s}^{-1}$
Magnetic diffusivity	$D_m = 3.5 \times 10^{-3} \text{ cm}^2/\text{s}$
Thermal diffusivity	$\chi = 2.7 \times 10^{-2} \text{ cm}^2/\text{s}$
Surface tension	$\alpha = 500 \text{ erg/cm}^2$
Thermal capacity	$c_p = 1.9 \times 10^7 \text{ erg/cm}^3\text{K}$
Sound speed	$S = 1.5 \times 10^5 \text{ cm/s}$
Volumetric thermal expansion coefficient	$\beta = 1.8 \times 10^{-4} \text{ K}^{-1}$

PROPERTIES OF CAPILLARY WAVES

[0023] Numerous studies on the theory of capillary waves exist. For the purpose of this application, however, a somewhat “non-traditional” slice of this theory, which cannot be found in one single publication, is needed. Therefore, this section is included. In all the numerical examples we will consider the mercury.

Ideal Liquid

[0024] Referring now to FIG. 2 a layer of a liquid 20 resting on a planar underlying surface 21 is shown. The substrate 21 is shaded. The surface of the film 20 is rippled at a wavelength λ $\lambda = 2\pi/k$. Dashed line 22 represents unperturbed surface of the film 20; δh is the amplitude of the surface perturbation.

[0025] The dispersion relation for a small-amplitude wave propagating over this surface is:

$$\omega^2 = \left(kg + \frac{\alpha k^3}{\rho} \right) \tanh(kh) \quad (\text{Equation 1})$$

[0026] The first term in the bracket in Equation 1 describes a contribution of gravity to the restoring force; the second term describes the contribution of surface tension. These two terms become equal at $k=k^*$, where

$$k^* = \sqrt{\frac{g\rho}{\alpha}} \quad (\text{Equation 2})$$

For mercury, this critical wave number is $k^* \approx 5 \text{ cm}^{-1}$ and corresponds to the wavelength of 1.2 cm.

[0027] FIGS. 3 and 4 show dispersion properties of surface waves in the setting of FIG.1. FIG. 3 shows dispersion curves for the mercury; curves, from the lower to the upper one, correspond to film thickness of 3 μm , 30 μm , and 100 μm , respectively; the dots show the points where the condition $\omega\tau=1$ is satisfied, where τ is defined by equation 8; to the lhs of the dots, the waves are strongly damped with the damping rate defined by equation 9. Dashed vertical line is the line where $k=k^*$.

[0028] FIG. 4 depicts dispersion relation for an arbitrary fluid presented in the dimensionless form, with ω measured in units of $(h/g)^{1/2}$, and k measured in units of $1/h$ ($\tilde{\omega} = \omega\sqrt{h/g}$, $\tilde{k} = kh$). In these units the dispersion relation (1) reads:

$$\tilde{\omega}^2 = \tilde{k} \left[1 + \frac{\tilde{k}^2}{(k^*h)^2} \right] \tanh \tilde{k} \quad (\text{Equation 1'})$$

Curves from the lower to the upper, correspond to the parameter k^*h equal to 10^{-1} , 10^{-2} , and 10^{-3} respectively.

[0029] For short wavelengths, $kh > 1$, the perturbation is localized near the free surface, and decays exponentially with the distance from the surface, with the e-folding length being $1/k$. The dispersion relation for such perturbations reads as:

$$\omega^2 = \left(kg + \frac{\alpha k^3}{\rho} \right) \quad (\text{Equation 3})$$

For these short waves, parallel and perpendicular (to the surface) displacements of liquid elements are of the same order of magnitude.

[0030] Long-wavelength perturbations, with $kh < 1$, occupy the whole layer.

The parallel to the surface displacements of liquid elements ($\xi_{||}$) are in this case much greater than perpendicular displacements (ξ_z). These displacements are:

$$\xi_z = z \frac{\delta h}{h} \cos(kx - \omega t); \xi_{||} = \frac{\delta h}{kh} \sin(kx - \omega t), \quad (\text{Equation 4})$$

where δh is the amplitude of the vertical displacement of the surface. The parallel component is independent of z (up to higher-order corrections in the parameter kh). As is clear from Equation (4), $\xi_{||} \sim \delta h / kh \gg \delta h$. The dispersion relation for long-wavelength ($kh < 1$) perturbations is

$$\omega^2 = \left(kg + \frac{\alpha k^3}{\rho} \right) kh \quad (\text{Equation 5})$$

[0031] The dispersion relation (1) describes also gravitational instability of the liquid film turned "upside down" so that the substrate is now at the top.

Dispersion relation in this case can be formally obtained from (1) by reversing the sign of g ,

$$\omega^2 = \left(-kg + \frac{\alpha k^3}{\rho} \right) \tanh(kh) \quad (\text{Equation 6})$$

Perturbations are stable (ω real) for short-enough wavelengths, $k > k^*$, and unstable otherwise.

[0032] Compressibility of the liquid is unimportant, because the phase velocity is typically much smaller than the sound velocity S . Indeed, for the mercury the phase velocity, $\sqrt{\alpha k / \rho}$, becomes formally greater than S only for unrealistically large k , $k > 5 \cdot 10^8 \text{ cm}^{-1}$.

Viscous Effects

[0033] Viscosity causes damping of stable perturbations. It cannot stabilize unstable perturbations with ($k < k^*$) in the case of inverted geometry but, in some cases, can reduce their growth rate.

[0034] In the case of short wavelengths, $kh > 1$, the damping rate $\text{Im} \omega$ is equal to:

$$\text{Im} \omega = -2 \nu k^2 \quad (\text{Equation 7})$$

For long wavelengths, $kh < 1$, the damping rate depends on the parameter $\omega \tau$, where τ is a characteristic time for viscous shear flow to propagate over the film thickness h ,

$$\tau \equiv \frac{h^2}{\nu} \quad (\text{Equation 8})$$

For a mercury film with $h = 25 \cdot \text{m}$, one has $\tau = 5.2 \cdot 10^{-3} \text{ s}$.

[0035] We will need the damping rate only for the case of small $\omega \tau$. In this domain, perturbations become essentially aperiodic, with $\text{Im} \omega \gg \text{Re} \omega$, and

$$\text{Im } \omega \approx -\frac{h^3 k^2}{3\nu} \left(g + \frac{\alpha}{\rho} k^2 \right) \quad (\text{Equation 9})$$

For the inverted configuration, and wavelengths with $k < k^*$, the system is unstable, with the growth rate being

$$\text{Im } \omega = \frac{h^3 k^2}{3\nu} g \left(g - \frac{\alpha}{\rho} k^2 \right) \quad (\text{Equation 10})$$

CREATING A LIQUID FILM BY PRESSING A LIQUID THROUGH A POROUS SUBSTRATE

General Approach

[0036] Referring to FIG. 1, the use of wettable and non-wettable substrates 12 is possible. The use of a non-wettable substrate would probably allow a complete removal of the liquid from the outer side of the system during the “in” move of the piston. A mechanical barrier (a rim) of the height approximately equal to the film thickness could be used to prevent the film from spreading laterally. For non-wettable substrate, the pressure in the liquid will be non-negative, so that there will be no concern about cavitation. A wettable substrate (with a non-wettable rim) is also conceivable. However, for the wettable substrate, one can expect that droplets will stick to the areas between the holes of the capillaries and the liquid will not be completely removed from the surface after every pulse. During the “in” motion of the piston, a negative pressure will develop, thereby creating a possibility of cavitation. On the other hand, the droplets will be absorbed by the liquid during the next pulse, and flat surface will be formed

again; also, the negative pressures developing during the "in" move are small and shouldn't lead to cavitation in a liquid of a normal purity. And, the wettable substrate would allow production of thinner films, with a thickness less than the size of capillaries.

[0037] Referring again to FIG. 1 one cycle of the motion of the piston will be described. Starting from the position where the liquid film 13 is present on the outer surface of the porous substrate 12. The piston 15 begins moving away from the substrate 12 and, by the end of a half-cycle, "sucks" the liquid 11 out of the capillaries into the volume behind the substrate 12. On the reverse motion, the piston 15 presses the liquid 11 through the capillaries and creates a liquid film 13 with a high-quality reflecting surface. The stroke of the piston 15 is equal to the thickness b of the substrate (plus the film thickness, which is usually negligible compared to b). It may suffice to have a stroke as small as a few thicknesses (h) of the liquid film. We, however, will discuss a more difficult in realization case of a larger stroke. This larger stroke may be necessary if one wants to extract all the working liquid from the capillaries during every cycle. A continuing lateral flow of the working liquid through a plenum behind the substrate could then be organized to gradually refresh it. A cleaning system can be introduced in this contour.

[0038] In one embodiment it is a porous unit. In another embodiment it is a porous substrate. In another embodiment it is a capillary substrate. In another embodiment it is planar. In another embodiment it is contoured. In another

embodiment it is a figured porous substrate. In another embodiment it comprises holes extending through said penetrable unit. In another embodiment it the holes are capillary size holes.

Deformations of the Substrate

[0039] In order to provide a smoothest possible surface of the mirror, the radius of capillaries, r_{cap} , must be made as small as possible. On the other hand, the pressure required to push the liquid through capillaries, Δp , increases as $1/r_{cap}$:

$$|\Delta p| = \frac{2\alpha}{r_{cap}} . \quad (\text{Equation 11})$$

For wettable materials one would have to apply a negative Δp to suck the liquid out of the capillary. When making the estimate (11), we considered perfectly non-wettable or perfectly wettable material, with the contact angle being either 180° or 0° . The pressure Δp applied to the substrate causes its deformation, which we will evaluate in this sub-section.

[0040] For the mercury,

$$\Delta p(atm) \approx \frac{10}{r_{cap}(\mu m)} . \quad (\text{Equation 12})$$

It is desirable not to make Δp too large, to avoid too strong deformation of the substrate; this pushes us in the direction of the larger radii r_{cap} . For the numerical example we choose $r_{cap} = 5 \mu m$. According to Equation 11, this corresponds to the pressure of 2 atm.

[0041] Returning to the issue of the cavitation touched upon the previous section, one can also note that the ram pressure generated in the liquid, ρv^2 , is small compared to the capillary pressure (12) and cannot contribute to the cavitation. Indeed, the maximum liquid velocity is $\sim 2\pi b/t_{piston}$ and, in for the aforementioned set of the numerical parameters is ~ 60 cm/s, yielding the maximum ram pressure of a mere 0.04 atm.

[0042] The maximum displacement Δb of the substrate occurs in its center.

Displacement amplitude is:

$$\Delta b = \frac{3(1 - \mu^2)R^4 \Delta p}{16b^3 E}, \quad (\text{Equation 13})$$

where R is the mirror radius, E is the Young's modulus, and μ is the Poisson coefficient of the substrate. To make an upper-bound estimate of Δb , we assume that E is 10 times less than the Young's modulus for the steel, i.e., we take $E = 2 \cdot 10^{10}$ n/m². With regard to μ , we take a value of 0.3, typical for many materials. Assuming, as before, that $R = 0.5$ cm, and $b = 0.1$ cm, we find that $\Delta b \sim 1$ μ m, the value that looks acceptable.

[0043] The characteristic frequency of the lowest mode of elastic vibrations of the substrate is :

$$\omega \sim \sqrt{\frac{b^2 E}{R^4 \rho}}, \quad (\text{Equation 14})$$

[0044] where ρ is the substrate density. Taking $\rho = 2$ g/cm³, and the other parameters as before, one finds that the resonant frequency is $\sim 10^5$ s⁻¹. The

presence of a heavy underlying liquid reduces this frequency by a factor of a few, leaving it still orders of magnitude higher than the frequency of the piston motion. This justifies using a steady-state approximation in evaluating Δb .

[0045] Rough estimates of displacement and of the lowest eigenfrequency for a rectangular membrane can be obtained by replacing R in Equations 13 and 14 by $(2L_1^{-2} + 2L_2^{-2})^{-1/2}$, where L_1 and L_2 are the lengths of the sides of the rectangle.

[0046] An additional force on the membrane will appear because of the viscous friction of the working liquid against the walls of the capillaries. It is assumed that liquid inside capillaries performs a vertical sinusoidal motion with the period t_{piston} and the amplitude $b/2$ (the distance between the upper and the lower position of the surface is then equal to the thickness of the substrate). This motion is driven by the piston. The amplitude of the viscous friction force between the walls and the liquid can be estimated as $2\pi^2 b^2 \nu \rho / t_{piston}$. The number of capillaries per unit surface area of the substrate is $\eta / \pi r_{cap}^2$, where η (~ 1) is a filling factor by which we mean the ratio of the area occupied by the holes to the total area of the substrate. Multiplying the two quantities, one finds additional pressure required to press the liquid through capillaries:

$$\Delta p_{visc} = \frac{2\pi\eta b^2 \nu \rho}{r_{cap}^2 t_{pist}}. \quad (\text{Equation 15})$$

For mercury, and $\eta=0.5$, $r_{cap}=5 \mu\text{m}$, $b=1\text{mm}$, and $t_{pist}=0.01\text{s}$ one finds that

$\Delta p_{visc} \sim 0.35 \text{ atm}$ and can be neglected compared to the pressure perturbation (12).

[0047] Two caveats are in order here. First, the real motion of the piston will probably be not a pure sinusoid. It might be worth adding a "plateau" on the dependence of the piston position vs time around the point where the thickness of the liquid film has reached a desired value. This would eliminate any unnecessary motions that could distort the surface of the film around the time when the optical pulse arrives. For the period of 0.01 s this plateau could probably be 0.002 s long. However, the presence of this relatively short plateau will have no significant effect on the estimate of the force (15). The second caveat is related to the fact that, when making estimate (15), it is implicitly assumed that the liquid flow in the capillary is a pure Poiseuille flow. In fact, the presence of the free surface of the liquid leads to a more complex 2D flow near the surface. We neglect this subtlety in our estimates because of a very large b/r_{cap} ratio.

The Waviness of the Reflecting Surface

[0048] The substrate is made of many capillaries closely packed together. It is assumed that the walls of the capillaries have a thickness of the order of r_{cap} ($\eta \sim 1$), the spatial scale of the surface structures can be estimated as r_{cap} . When the liquid is pressed through the capillaries, its surface gets rippled at this scale or, in other words, the ripples have a characteristic wave number $k \sim 1/r_{cap}$. These ripples experience a rapid viscous damping described by Equation. (7). For mercury and $r_{cap} = 5$ microns one has $\text{Im}\omega \sim 10^4 \text{ s}^{-1}$; in other words, these perturbations damp away during a small fraction of the in-out period. Generally speaking, initial perturbations will have a broad spectrum where also longer wavelengths will be

present. Specific details of the spectrum will be determined by possible larger-scale correlations between positions of individual capillaries. These correlations will depend on the manufacturing process and are unknown to us at this stage. One can only say that even perturbations with spatial scales $\sim 10r_{cap}$ decay relatively quickly, within $\sim 10^2$ s.

[0049] A special class is formed by long-wave perturbations with $k < k^*$, which are unstable for the upside-down orientation. The finite radius of the mirror limits wave number of perturbations from below, by the value approximately equal to

$$k_{min} = 1.5/R \quad (\text{Equation 16})$$

(the exact numerical coefficient depends on the boundary conditions on the rim).

For mercury, and $R=0.5$ cm, the unstable mode is indeed present ($k_{min} < k^*$).

However, it grows very slowly because of the viscous effects. Indeed, Equation (10) shows that for a $25 \mu\text{m}$ thick mercury film, and $k=3 \text{ cm}^{-1}$, the growth rate is $6 \cdot 10^{-2} \text{ s}^{-1}$. The corresponding e-folding time is 15s, much longer than the period of the piston motion. For a rectangular mirror with the lengths of the sides equal to L_1 and L_2 , under the assumption that displacement is zero on the boundaries, the minimum wave number is

$$k_{min} = \pi \sqrt{\frac{1}{L_1^2} + \frac{1}{L_2^2}} \quad (\text{Equation 17})$$

[0050] Although the instability by itself is not a big problem (because of its small growth rate), the absence of the restoring force for the perturbations with

$k < k^*$ means that at the large scales the film must be perfect during the whole time of its creation, with tilts or bumps with a scale $k < k^*$ being inadmissible. This means that the properties of the porous substrate must be uniform to a high level of precision at these scales.

[0051] As the long-wavelength instability is so slow, it is not a limiting factor in the increase of the size of the mirror. The uniformity of the substrate at larger scales may pose more serious problems.

[0052] Conversely, if one wants to have a mirror that would be stable for all perturbations, and whose surface would experience restoring forces bringing the surface to an equilibrium shape (thereby relaxing requirements to the quality of the substrate), one might want to reduce its radius R to the values below, roughly speaking, $1.5/k^*$ (3 mm for mercury). The problem is that the equilibrium shape for a small mirror will not be planar, but will be a meniscus. Referring now to FIG. 5, the making of a quasiplanar mirror in this case by introducing correcting electrostatic forces is illustrated. A quasiplanar mirror is formed near the center of the meniscus. An electric field is created between the correcting electrode 41 and the liquid mirror 43. The solid line 43 depicts initial surface of the meniscus; dashed line 44 shows a corrected surface, after the voltage is applied; this corrected surface 44 is nearly planar near the axis. A supporting structure 42 supports the liquid. A supporting structure 42 operatively retains the liquid 44. The supporting structure 44 may comprise a penetrable unit. The minimum possible level of deviations of the mirror surface

from planarity in the stable domain is determined by thermal fluctuations. The spectral energy density W_k of thermal fluctuations is defined by the equation:

$$dW = W_k dk_x dk_y \quad (\text{Equation 18})$$

where dW is the energy of surface oscillations in the interval of wave numbers dk_x , dk_y per unit surface area of the plane. For thermal fluctuations, one has

$$W_k = \frac{\kappa_B T}{(2\pi)^2} \quad (\text{Equation 19})$$

(the Rayleigh-Jeans distribution, with T and k_B being the temperature of the film and the Boltzmann constant, respectively). On the other hand, W_k is related to the spectral density of surface displacements $(\xi^2)_k$ via equation:

$$W_k = \frac{(\xi^2)_k \omega_k^2 \rho}{k} \cdot \frac{\sinh(2kh)}{\cosh(2kh) - 1} = (\xi^2)_k (\rho g + \alpha k^2) \quad (\text{Equation 20})$$

(we have used dispersion relation (1)). Equations (19)-(20) then yield the following expression for the contribution $d\bullet$ of the interval dk_x, dk_y to the mean-square deviation of the surface from the plane:

$$d\xi^2 \equiv (\xi^2)_k dk_x dk_y = \frac{\kappa_B T}{(2\pi)^2 (\rho g + \alpha k^2)} \cdot dk_x dk_y \quad (\text{Equation 21})$$

Remarkably, this result coincides with the previously derived expression for $d\xi^2$ for the liquid of an infinite depth. For capillary waves (i.e., the waves with $k > k^*$, Equation (2)), one obtains:

$$d\xi^2 \equiv \frac{\kappa_B T dk}{2\pi k \alpha} \quad (\text{Equation 22})$$

We have taken into account that $dk_x dk_y = 2\pi k dk$. The contribution to the surface roughness from the wave numbers whose absolute values lie between k_1 and k_2 is:

$$\xi^2(k_1 < k < k_2) = \frac{\kappa_B T}{2\pi\alpha} \ln\left(\frac{k_2}{k_1}\right) \quad (\text{Equation 23})$$

The longer wavelengths, $k < k^*$, give smaller contribution. One sees that for a rough estimate of the r.m.s. value for deviations from planarity one can use an equation

$$\sqrt{\langle \xi^2 \rangle} \approx \sqrt{\frac{5\kappa_B T}{2\pi\alpha}} \quad (\text{Equation 24})$$

where we have replaced the logarithmic factor by its typical numerical value ~ 5 . For mercury at the temperature $\sim 300^\circ\text{K}$, one has $\sqrt{\langle \xi^2 \rangle} \sim 1 \text{ \AA}$. This determines the minimum possible surface roughness. The actual roughness may be somewhat larger than (24) because of the finite size of atoms (or molecules) forming the liquid.

The Role of Vibrations

[0053] High-precision optical elements installed on an experimental facility usually experience some level of vibrations originating from external sources. There is an issue of possible misalignment caused by these vibrations. For the optical systems a great experience has been accumulated in dealing with this problem. In this sense, solid elements of the system discussed above (e.g., substrates) do not create any specific new problems. A question may arise, though, on how vibrations could affect liquid surfaces.

[0054] Typical frequencies of vibrations, ω_{vibr} , lie in the range below 300 s^{-1} .

They are below the eigenfrequencies of the substrate (Equation 24)). We therefore assume that the substrate moves as a perfectly rigid body. This motion can be represented as a superposition of translational motion and tilts.

[0055] Translations are first considered. They are characterized by a displacement vector $\xi(t)$. The translational acceleration $d^2\xi/dt^2$ can be represented as a sum of the tangential and normal acceleration. The normal acceleration does not change the shape of a planar surface of the mirror. So, they are considered tangential acceleration. It causes a liquid flow along the surface of the mirror and leads thereby to tilting of the liquid surface. For relatively low frequencies mentioned above and thin-enough films, the condition $\omega_{\text{vibr}}\tau < 1$ holds (where τ is defined as in (8)), meaning that the tangential velocity is a linear function of the distance from the substrate surface (Couette flow), with the average (over the film thickness) velocity equal to

$$\bar{v} = \frac{\tau d\xi_t/dt}{2}, \quad (\text{Equation 25})$$

where by ξ_t it is meant only tangential component of the displacement. This flow causes increase of the depth on one side of the mirror and decrease on the other side. The estimate for the relative displacement Δh of the liquid surface at two opposite sides of the disk then follows,

$$\Delta h \sim \frac{h\omega_{\text{vibr}}^2 \xi \tau}{R} \min(\omega_{\text{vibr}}^{-1}, \Delta t) \quad (\text{Equation 26})$$

where Δt is a time interval during which thin film exists at the outer surface of the substrate (0.03 s in the example given). It was deliberately overestimated Δh by writing ξ instead of ξ_i .

[0056] The tilt of the surface of the film relative to the substrate is $\Delta h/R$. In order to be unimportant, it must be less than the tilt of the substrate itself, θ . The latter is related to the displacement by $\theta \sim \xi/L$, where L is the size of the structural element of the facility to which the mirror system is attached, or the wavelength of vibrations in this element, if the latter is shorter. In this way it is possible to arrive at the following criterion for unimportance of specifically "liquid" effects in vibrations:

$$\frac{hL\omega_{\text{vibr}}^2\tau}{R^2} \min(\omega_{\text{vibr}}^{-1}, \Delta t) < 1 \quad (\text{Equation 27})$$

As already mentioned, for thin-enough films, one has $\omega_{\text{vibr}}\tau < 1$. This means that condition (27) is certainly satisfied if $hL < R^2$; for our standard set of parameters, $R=0.5$ cm, $h=25$ microns, this latter inequality holds if $L < 100$ cm.

[0057] The normal component of the acceleration does not affect the planar surface of the liquid film but it may affect the curved surface of the type we discuss in the next section. It is also worth noting that tilts of the substrate cause smaller tilt of the liquid surface relative to substrate than tangential accelerations we have just discussed.

Maximum Intensity of the Laser Pulse

[0058] There are two limitations on the intensity of the laser pulse that can still be handled by the system without damaging its permanent components. The first is decrease of the reflectivity during the laser pulse itself (because of, e.g., bringing the surface to a boil temperature during the pulse). The second is possible damage to the substrate by mechanical and thermal perturbations initially produced near the surface of the liquid and then propagating towards the substrate. The first constraint is not specific to the concept. There exist numerous studies of that issue. Therefore only the second constraint is discussed, limited to a qualitative discussion. Consider a 1-dimensional problem, assuming that the spot size on the surface of the film is greater than the film thickness.

[0059] There are two characteristic times important in the problem, the sound propagation time through the film, h/S (where S is the sound velocity), and the time of a thermal diffusion, h^2/χ (where χ is thermal diffusivity). For a 25 μm -thick mercury film, the acoustic time is $\sim 2 \cdot 10^{-8}$ s, and the thermal conduction time is $\sim 2 \cdot 10^{-4}$ s.

[0060] The characteristic pulse-width of the x-ray pulse in the LCLS project is in the range of 200-300 fs. As the laser pulse is shorter than the acoustic time, the pressure perturbation created near the surface, propagates as an acoustic pulse (which may become a shock wave, if the amplitude is large enough). The energy deposition occurs at a depth $\Delta h \sim 0.3 \mu\text{m}$ in mercury (this is determined by photo-absorption of x rays and subsequent energy transport by keV-range

electrons). The liquid within this layer is heated up to some temperature ΔT virtually instantaneously (compared both to the sound propagation time and the heat conduction time over Δh). The resulting pressure perturbation Δp_0 then drives an acoustic pulse propagating towards the substrate. It may form a weak shock by the familiar overtaking process. The shock is formed if the condition

$$\Delta p_0 > \rho S^2 \frac{\Delta h}{h} \quad (\text{Equation 28})$$

holds. By noting that the pressure perturbation in the isochoric heating can be evaluated as

$$\Delta p_0 \sim \rho S^2 \beta \Delta T \quad (\text{Equation 29})$$

(where μ is volumetric thermal expansion coefficient), one finds that the shock is formed if

$$\Delta T > \frac{\Delta h}{\beta h} \quad (\text{Equation 30})$$

For mercury in the aforementioned example, the shock is formed if $\Delta T > 50$ K.

This corresponds to the deposited energy $C_p \Delta h \Delta T > 3 \text{ mJ/cm}^2$.

[0061] If the shock is indeed formed, it weakens during its propagation through the film [9]; the pressure jump at the distance h from the surface decreases to $\Delta p \sim \Delta p_0 \sqrt{(\rho S^2 / \Delta p_0)(\Delta h / h)} < \Delta p_0$, the last inequality being a consequence of (28). For the energy deposition in the range of the critical value of 3 mJ/cm^2 , the expected pressure amplitude will be in the range of 3 Kbar, somewhat below the yield strength of good structural materials.

[0062] For longer-pulse, higher energy-per-pulse lasers, the favorable regimes of operation are those where the pulse width is larger than the sound propagation time h/S , so that thermal stresses in the heated surface layers increase adiabatically slowly, and do not lead to shock formation. They just cause a quasi-equilibrium thermal expansion of the heated layer, with only small pressure increase in the bulk of the film. If the pulse is shorter than h/S , it is at least desirable to make it longer than $\Delta h/S$. The pressure perturbation in the pressure pulse that will be propagating towards the substrate will then be much less than Equation 29).

ELECTROSTATICALLY CONTROLLED MIRRORS

Mirror Focal Length

[0063] FIG. 6 illustrates creating a focusing mirror by introducing an electrostatic field between the liquid and the ring. In other embodiments more sophisticated sets of electrodes can be used, including electrodes segmented in the azimuthal direction. As shown in FIG. 6, another CAMEL configuration generally designated by the reference numeral 50, is a parabolic mirror 51 in a thin layer of a liquid 52, with a substrate 53 being a flat porous conducting plate. A ring electrode 54 of a radius R will be situated at some distance ($\sim R$) over the surface 51. Electric field will distort the surface of the liquid, with the region near the axis forming a parabolic mirror. If a thin ring is situated at a distance a from the surface of the plate, the electric field at the planar surface of the conducting liquid (kept at the ground potential) is determined by the equation

$$E_z(r) = \frac{2URa}{\Lambda} \int_0^\pi \frac{d\varphi}{(a^2 + R^2 - 2Rr \cos\varphi + r^2)^{3/2}} \quad (\text{Equation 31})$$

where U is the ring potential, and Λ is a logarithmic factor depending on the (small) thickness d of the ring [$\Lambda \approx \ln[2\min(a, R)/d]$]; r is the distance from the axis of symmetry. Under the action of a ponderomotive force, the surface becomes perturbed. However, these perturbations are small (at least for the mirrors with the focal distance much greater than the mirror radius). We will neglect these small corrections when evaluating E_z . If there is a need to refresh the liquid between the two subsequent pulses, one can use a conducting, porous substrate.

[0064] For large-focal-length mirrors deviations of the surface from planarity are small, $\Delta h \ll R$, and one can use the linear equation to find Δh :

$$\frac{\alpha}{r} \frac{d}{dr} r \frac{d\Delta h}{dr} = \rho g \Delta h - \frac{E_z^2}{8\pi} \quad (\text{Equation 32})$$

We will study its solution near the axis, at small r . In this zone the ponderomotive force can be presented as an expansion:

$$\frac{E_z^2}{8\pi} = \frac{\pi(Ua)^2}{2\Lambda^2(a^2 + R^2)^3} \left[1 + C_1 \left(\frac{r}{R} \right)^2 + C_2 \left(\frac{r}{R} \right)^4 + \dots \right] \quad (\text{Equation 33})$$

We limit ourselves to the first three members. One has:

$$C_1 = \frac{3R^2(3R^2 - 2a^2)}{2(a^2 + R^2)^2}; C_2 = \frac{3R^4 \left(4a^4 - 17a^2R^2 - \frac{329}{64}R^4 \right)}{2(a^2 + R^2)^4} \quad (\text{Equation 34})$$

If we are interested in not-too-small mirrors, with the size exceeding $1/k^*$, one can neglect capillary forces and set the left hand side (l.h.s.) of Equation 32 to

zero. Then one obtains the following expression for the function $\Delta h(r)$:

$$\Delta h(r) = \frac{\pi(Ua)^2}{2\rho g\Lambda^2(a^2 + R^2)^3} \left[1 + C_1\left(\frac{r}{R}\right)^2 + C_2\left(\frac{r}{R}\right)^4 + \dots \right] \quad (\text{Equation 35})$$

If corrections related to the finite value of the capillary forces are required, one can find them by substituting this solution to the l.h.s. of Equation 32. The ideal parabolic mirror corresponds to all the terms beyond r^2 being equal to zero. The focal length in the paraxial domain, where the third and higher-order terms in the R.H.S. of (35) can be neglected, is

$$F = \frac{\rho g\Lambda^2(a^2 + R^2)^5}{3\pi(Ua)^2(3R^2 - 2a^2)} \quad (\text{Equation 36})$$

[0065] At given voltage U and radius R of the ring, the focal length varies as a function of the distance a between the ring and the surface. Assuming that the ring thickness d is small, we neglect a weak logarithmic dependence of Λ vs a). At small a , the surface near the axis is almost flat, and the focal length is infinite. It reaches a minimum at the distance $a \approx 0.45R$. At the further increase of a , the surface near the axis again becomes flat (at $a = 1.22R$), and then becomes convex, giving rise to a defocusing mirror. The minimum focal length for the defocusing mirror is attained at $a \approx 1.57R$. Finally, at even larger a 's, the surface again flattens.

[0066] At the distance $a \approx 0.45R$ corresponding to the minimum focal length, one has

$$F = F_0 \equiv \frac{0.51\rho g\Lambda^2 R^6}{U^2} \quad (\text{Equation 37})$$

Equation 37 shows that, with mercury as the working liquid, creating a mirror with a focal length of 50 cm by a ring of the radius $R=0.5$ cm requires a modest voltage ~ 1.5 kV (we assumed $\epsilon=3$). With this voltage, the maximum value of Δh (which is reached just under the ring, at $r \approx R$) is approximately $30 \mu\text{m}$. This sets the minimum value of the initial thickness of the liquid film, which must be greater than $\sim 30 \mu\text{m}$. Note that a voltage of 1.5 keV over a gap of ~ 0.5 cm will not cause a breakdown even for an electrode without special surface treatment.

[0067] One advantage of this scheme is that it works not only for conducting but also for dielectric liquid (for the latter, the result analogous to Equation 4.5 will also depend on the dielectric constant). Another advantage is related to a possibility of using several ring electrodes segmented in the azimuthal direction, each with an independent voltage control. By proper adjustment of the voltages applied to azimuthal segments, one can create an approximately parabolic mirror with an axis tilted with respect to the normal to the surface. This demonstrates one outstanding feature of the CAMEL concept: remote control of the focal length and optical axis of a figured mirror, without introducing any mechanically moving parts.

[0068] In the aforementioned embodiment, the electrode in front of the mirror limits the solid angle that can be used for collecting light. For dielectric liquids, one can eliminate this constraint by using a ring situated below the liquid film and dielectric substrate. This additional embodiment of a system incorporating the present invention is illustrated in FIG. 7 wherein a ring 61 is situated below

the liquid film 62 and dielectric substrate 63. Liquid dielectric with a dielectric constant ϵ_1 is situated above the substrate 63 with a dielectric constant ϵ_2 . The unperturbed surface of the liquid is shown by a dashed line 64. After voltage is applied to a ring electrode 61 of a radius R , the surface becomes distorted and, near the axis, acquires the shape of a focusing mirror. The second electrode is situated far from the ring.

Characteristic Time-Scales for Changing the Shape of the Mirror

[0069] Consider a pool of liquid of the thickness $h \ll R$. If one wants to vary the focal length and orientation of the optical axis by varying the voltages at different electrodes, one has to evaluate the characteristic time τ_{response} within which the liquid will redistribute itself over the surface of the substrate and settle down in the new equilibrium. For thin films, viscous forces may be important and could slow down the response time. Basically, this time is equal to the time of viscous damping of surface waves with the wave-number $k \sim 1/R$. For not too thick films, the damping rate is determined by Equation 9, with the 1st term neglected (because we assume that $kR \gg 1$) According to the estimate (9), we have

$$\tau_{\text{response}} \sim \frac{2\nu R^2}{h^3 g} \quad (\text{Equation 38})$$

For a mercury mirror with $R=0.5$ cm and $h=30$ μm , one finds $\tau_{\text{response}} \sim 20$ s.

According to Equation 38, the response is faster for thicker mirrors. At some point, however, the response time evaluated according to Equation 38 becomes shorter than the viscous time (8), and applicability conditions of Equation 9 (or,

equivalently, Equation 38) break down. The maximum thickness at which one can still use Equation 38 can be evaluated from the condition $\tau_{response} \sim \tau$ (with τ as in Equation 8), which yields:

$$h \sim \left(\frac{2v^2 R^2}{g} \right)^{1/5} \quad (\text{Equation 39})$$

The corresponding response time is

$$\tau_{response} \sim \left(\frac{4R^4}{g^2 v} \right)^{1/5} \quad (\text{Equation 40})$$

For the mercury mirror with $R=0.5$ cm, one has $h=150$ m, and the corresponding shortest response time ~ 0.2 s.

[0070] For the film thicker than the one evaluated from Equation 39, the response will be accompanied by excitation of the wave motion of the liquid. One could significantly reduce the amplitude of transient waves by applying the voltage in an “adiabatically slow” fashion. How much one can gain then in terms of the response time, will be analyzed in further reports. Too thick films, on the other hand, may be too vulnerable to vibrations.

MAGNETICALLY CONTROLLED MIRRORS

[0071] The $\mathbf{j} \times \mathbf{B}$ force can be used to prevent the liquid from sliding down along the surface of a tilted flat substrate. This may be required, if one needs to create a renewable quasi-steady-state planar mirror. The schematic of a liquid mirror in this case is shown in FIG. 8. The presence of a large permanent magnetic field \mathbf{B} normal to the surface 71 allows one to reduce requirements to

the current that flows across this field, and thereby make the Joule heating of the film insignificant.

[0072] The concept illustrated by FIG. 9 can be used to make a small renewable focusing (defocusing) mirror. Two concentric electrodes, electrode 81 and ring electrode 82, are introduced into the liquid film. The substrate 83 is in this case is dielectric and the substrate 83 is a porous substrate as previously described. The radial current flowing between the inner and outer electrodes, generates the azimuthal magnetic field. The $j \times B$ force arises which is directed upward and which causes a perturbation of the surface. The working part of the mirror surface will be situated near the axis, where one can create a profile close to a parabolic profile. The magnetic field strength required to produce a 30- μm variation of the thickness of the film in the mirror of 0.5 cm radius is modest, for the mercury it is ~ 30 G; this corresponds to a modest current ~ 100 A.

DESCRIPTION OF ADDITIONAL EMBODIMENTS

[0073] Referring to FIG. 10, another embodiment of a system incorporating the present invention is illustrated. The system is generally designated by the reference numeral 140. The system 140 provides a planar renewable mirror. An actuator 141 is connected to a flexible membrane 142. The actuator 141 and flexible membrane 142 are carried by mechanical support 143. A liquid fills plenum 144. The reflecting liquid film 1 (5-50 gm thick) is formed by pressing the working fluid 144 through the porous substrate 145 by the actuator 141 and flexible membrane 142. Before the gravitational instability of the free surface of

the liquid has developed, the actuator 141 and flexible membrane 142 sucks the liquid back to the plenum, and the cycle repeats. Specific instability time is determined by the properties of the fluid and the thickness of the film. The free surface of the planar mirror will not suffer from deformations caused by this instability for the time intervals in the range from 0.01 to 0.1 s. The substrate should be --1 mm thick to assure sufficient stiffness against deformations caused by the motion of the liquid through it.

[0074] The working liquid shown in FIG. 10 is mercury. In another embodiment of the invention the working liquid is gallium. In other embodiments of the invention the working fluid is composed other materials that provide reflectivity. In other embodiments of the invention the working fluid is composed other materials that provide reflectivity. The working fluid in other embodiments can be conducting liquids including Gallium; NaK alloy (40 to 90% of K). The working fluid in other embodiments can be dielectric liquids including various alcohols, from ethyl alcohol C_2H_6O to benzyl alcohol C_7H_8O ; glycerin; heavy carbohydrates, like C_9H_{20} .

[0075] Another embodiment of the system is shown in FIG. 11. The system is generally designated by the reference numeral 150. The system 150 provides a planar renewable mirror. A bellows 151 is held in place by stiff ring 153. A liquid fills plenum 152. One cycle of the motion of the system will be described. The bellows 151 begins moving the liquid out of the plenum 152. On the reverse motion,

the bellows 151 presses the liquid through the capillaries and creates a liquid film with a high-quality reflecting surface.

[0076] A modification of this system is a mirror formed over a shaped substrate shown in FIG. 12, which illustrates formation of a curved mirror 164 in a "normal" orientation. The flow of liquid under the action of the gravity force is slow because of viscous friction. In some configurations, if necessary, this flow can be stopped altogether by applying a properly oriented $j \times B$ force.

[0077] Referring again to FIG. 12, an embodiment of a system incorporating the present invention is illustrated. The system is generally designated by the reference numeral 160. The system 160 provides a contoured renewable mirror. A piston 161 moves the working liquid 162 within a mechanical support. A figured porous substrate 163 is located on the other side of the working liquid 162 from piston 161. In another embodiment the figured porous substrate comprises holes extending entirely through the penetrable unit. In another embodiment the holes are capillary size holes.

[0078] One cycle of the motion of the piston 161 will be described starting from the position where the contoured film 164 is present on the outer surface of the figured porous substrate 163. The piston 161 begins moving away from the substrate 163 and, by the end of a half-cycle, "sucks" the liquid out of the capillaries behind the substrate 163. On the reverse motion, the piston 161 presses the liquid through the capillaries and creates a contoured liquid film reflecting system with a high-quality reflecting surface.

[0079] While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and have been described in detail herein. However, it should be understood that the invention is not intended to be limited to the particular forms disclosed. Rather, the invention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.

4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215